


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 65.74 lm/W			
MODEL	3000K CRI90	I _{max} (cd)	8458	S/MH(C0/180)	0.29
NOMINAL POWER(W)	11	LOR(%)	100.0	S/MH(C90/270)	0.25
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	710.03	η UP,DN(C0-180)	0.0,50.1
NOMINAL FLUX(lm)	710.03	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.9
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	230	η down(%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1833	1990	2265	2873	3039	2622	2214	1855	0- 10	443.5	443.5	62.5, 62.5
20	141.0	163.8	166.6	237.8	287.9	210.3	153.4	128.2	10- 20	215.9	659.4	92.9, 92.9
30	25.27	24.81	28.03	34.18	39.45	31.65	28.22	23.93	20- 30	34.16	693.6	97.7, 97.7
40	9.095	8.184	9.284	12.16	13.56	9.543	8.107	9.375	30- 40	10.34	703.9	99.1, 99.1
50	2.206	2.040	2.230	4.173	3.520	2.468	2.038	2.394	40- 50	4.653	708.6	99.8, 99.8
60	0.3545	0.3588	0.3610	0.8060	0.9711	0.5086	0.3784	0.4825	50- 60	1.159	709.7	100, 100
70	0.0235	0	0	0	0.0784	0.1231	0.1619	0.1341	60- 70	0.1638	709.9	100, 100
80	0.0704	0.0782	0.0232	0.0275	0.0705	0.0985	0.0820	0.1156	70- 80	0.0675	709.9	100, 100
90	0.2116	0.1992	0.1877	0.1842	0	0	0	0	80- 90	0.0847	710.0	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 706.86 lm

%lum = 99.6%

%lamp = 99.6%

Conical surface Flux(120deg): 709.71 lm

%lum = 100.0%


%lamp = 100.0%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1102	973
80	292	97
75	66	0
70	50	0
65	60	0
60	511	522
55	1289	1225
50	2476	2508
45	4885	5208


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.14	1.12	1.11	1.12	1.10	1.09	1.08	1.07	1.06	1.04	1.03	1.03	1.01	1.00	.00	.98
2.0	1.10	1.07	1.05	1.08	1.06	1.04	1.05	1.03	1.02	1.02	1.01	.00	.00	.99	.98	.96
3.0	1.06	1.04	1.01	1.05	1.03	1.00	1.03	1.01	.99	1.01	.99	.97	.99	.97	.96	.95
4.0	1.04	1.00	.98	1.03	.00	.97	1.01	.98	.96	.99	.97	.95	.97	.96	.94	.93
5.0	1.01	.98	.95	1.00	.97	.95	.99	.96	.94	.97	.95	.93	.96	.94	.93	.92
6.0	.99	.96	.93	.98	.95	.93	.97	.94	.92	.96	.94	.92	.95	.93	.91	.90
7.0	.97	.94	.91	.96	.93	.91	.95	.93	.91	.94	.92	.90	.93	.91	.90	.89
8.0	.95	.92	.90	.95	.92	.90	.94	.91	.89	.93	.91	.89	.92	.90	.89	.88
9.0	.93	.90	.88	.93	.90	.88	.92	.90	.88	.92	.89	.88	.91	.89	.87	.87
10.0	.92	.89	.87	.92	.89	.87	.91	.89	.87	.91	.88	.87	.90	.88	.86	.86



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm					
NAME: ALST45-11G30-S			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:38		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.116	.066	.021	.109	.062	.020	.097	.056	.018	.086	.049	.016	.075	.044	.014	
2.0	.105	.058	.018	.100	.055	.017	.090	.050	.016	.081	.045	.014	.072	.041	.013	
3.0	.096	.051	.015	.092	.049	.015	.084	.045	.014	.076	.042	.013	.069	.038	.012	
4.0	.089	.046	.014	.085	.045	.013	.078	.042	.012	.072	.039	.012	.066	.036	.011	
5.0	.083	.042	.012	.080	.041	.012	.074	.038	.011	.068	.036	.011	.063	.034	.010	
6.0	.077	.039	.011	.075	.038	.011	.070	.036	.010	.065	.034	.010	.061	.032	.010	
7.0	.073	.036	.010	.070	.035	.010	.066	.033	.010	.062	.032	.009	.059	.030	.009	
8.0	.068	.033	.009	.067	.033	.009	.063	.031	.009	.060	.030	.009	.056	.029	.008	
9.0	.065	.031	.009	.063	.031	.009	.060	.030	.008	.057	.029	.008	.054	.028	.008	
10.0	.062	.030	.008	.060	.029	.008	.057	.028	.008	.055	.027	.008	.052	.026	.008	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.167	.158	.150	.143	.135	.129	.098	.093	.089	.056	.054	.052	.018	.017	.017	
2.0	.147	.133	.121	.126	.114	.104	.086	.079	.073	.050	.046	.043	.016	.015	.014	
3.0	.131	.113	.099	.112	.098	.086	.077	.068	.060	.045	.040	.035	.014	.013	.012	
4.0	.117	.097	.082	.101	.084	.071	.069	.059	.050	.040	.034	.030	.013	.011	.010	
5.0	.106	.085	.069	.091	.073	.060	.063	.051	.042	.036	.030	.025	.012	.010	.008	
6.0	.096	.074	.059	.083	.064	.051	.057	.045	.036	.033	.027	.022	.011	.009	.007	
7.0	.088	.066	.050	.075	.057	.044	.052	.040	.031	.030	.024	.019	.010	.008	.006	
8.0	.081	.059	.044	.069	.051	.038	.048	.036	.027	.028	.021	.016	.009	.007	.005	
9.0	.074	.053	.038	.064	.046	.033	.044	.032	.024	.026	.019	.014	.008	.006	.005	
10.0	.069	.048	.033	.060	.041	.029	.041	.029	.021	.024	.017	.012	.008	.006	.004	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm											
NAME: ALST45-11G30-S					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:38			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	4.9	5.4	5.1	5.5	5.7	5.1	5.6	5.3	5.8	5.9	
	3H	4.7	5.2	5.0	5.4	5.6	5.0	5.5	5.2	5.6	5.8
	4H	4.7	5.1	4.9	5.3	5.5	4.9	5.4	5.2	5.6	5.8
	6H	4.6	5.0	4.9	5.3	5.5	4.8	5.3	5.1	5.5	5.7
	8H	4.6	5.0	4.9	5.2	5.5	4.8	5.2	5.1	5.5	5.7
	12H	4.6	5.0	4.9	5.3	5.5	4.8	5.2	5.1	5.5	5.7
4H	2H	4.7	5.2	4.9	5.4	5.6	4.9	5.4	5.2	5.6	5.8
	3H	4.5	4.9	4.8	5.2	5.4	4.8	5.2	5.1	5.4	5.7
	4H	4.4	4.8	4.8	5.1	5.4	4.7	5.1	5.0	5.3	5.6
	6H	4.4	4.7	4.7	5.0	5.3	4.6	4.9	4.9	5.2	5.6
	8H	4.3	4.7	4.7	5.0	5.4	4.5	4.9	4.9	5.2	5.6
	12H	4.4	4.7	4.8	5.1	5.4	4.6	4.9	5.0	5.2	5.6
8H	4H	4.3	4.6	4.7	4.9	5.3	4.5	4.8	4.9	5.2	5.5
	6H	4.2	4.5	4.6	4.8	5.2	4.4	4.7	4.8	5.1	5.5
	8H	4.2	4.4	4.7	4.9	5.3	4.4	4.6	4.8	5.0	5.5
	12H	4.4	4.6	4.8	5.0	5.5	4.5	4.7	4.9	5.1	5.6
12H	4H	4.2	4.5	4.6	4.9	5.3	4.5	4.8	4.9	5.1	5.5
	6H	4.1	4.4	4.6	4.8	5.2	4.4	4.6	4.8	5.0	5.4
	8H	4.2	4.4	4.6	4.8	5.3	4.4	4.6	4.8	5.0	5.5
Variations with the observer position at spacings:											
S = 1.0H	+ 2.8 / - 7.5					+ 2.8 / - 8.6					
1.5H	+ 4.3 / - 6.1					+ 4.3 / - 6.2					
2.0H	+ 6.0 / - 7.1					+ 6.3 / - 8.9					

CIE Pub.117, 710.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.2)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	91	85	82	91	85	82	90	85	82	79
0.80	98	93	90	97	92	89	96	92	89	86
1.00	102	97	94	101	96	93	99	96	93	89
1.25	105	101	98	104	100	97	102	99	96	93
1.50	108	103	101	107	103	100	104	101	99	95
2.00	110	106	103	108	105	102	106	103	101	96
2.50	111	108	105	110	107	104	107	104	102	97
3.00	113	110	107	111	108	106	108	106	104	98
4.00	115	112	110	113	110	109	109	107	106	99
5.00	116	114	112	114	112	111	110	109	107	100
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

AAI Figure

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:225.1V I:0.0530A P:10.80W PF:0.9070 Freq:0Hz Lamp Flux:710.03x1 lm		
NAME: ALST45-11G30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:38	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	107
L_0~180 (75) av	153
L_0~180 (85) av	568
L_90~270 (65) av	167
L_90~270 (75) av	180
L_90~270 (85) av	486
L_45 (65) av	124
L_45 (75) av	179
L_45 (85) av	642

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-10-29

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: AE
Test Date: 2020-10-29

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```