

Cylinder series


TL45-S-15W

optical lens



Technical Parameters:

Name	Parameters
Light source:	COB
Input Voltage:	AC220~240V 50/60Hz
LED Current:	350mA, 35-37V
Beam Angle:	12°/24°/36°/60°
Life Time:	> 50,000h - L80 - B10 (Ta 25° C)
Operating temperature:	-20°C~40°C
Certificate:	CE/RoHS
Weight:	0.35kg



Ordering Information:

○ White ● Black




Power	CRI	Beam Angle	Luminous	CCT	Housing	Part Number
15W	>80	▲ 12°	1500 lm	3000K	○	TL45*-15W-830-W-12-S
					●	TL45*-15W-830-B-12-S
		1600 lm	4000K	○	TL45*-15W-840-W-12-S	
				●	TL45*-15W-840-B-12-S	
		▲ 24°	1480 lm	3000K	○	TL45*-15W-830-W-24-S
					●	TL45*-15W-830-B-24-S
	1580 lm	4000K	○	TL45*-15W-840-W-24-S		
			●	TL45*-15W-840-B-24-S		
	▲ 36°	1520 lm	3000K	○	TL45*-15W-830-W-36-S	
				●	TL45*-15W-830-B-36-S	
	1650 lm	4000K	○	TL45*-15W-840-W-36-S		
			●	TL45*-15W-840-B-36-S		
>90	▲ 12°	1270 lm	3000K	○	TL45*-15W-930-W-12-S	
				●	TL45*-15W-930-B-12-S	
		1370 lm	4000K	○	TL45*-15W-940-W-12-S	
				●	TL45*-15W-940-B-12-S	
		▲ 20°	1260 lm	3000K	○	TL45*-15W-930-W-24-S
					●	TL45*-15W-930-B-24-S
	1350 lm	4000K	○	TL45*-15W-940-W-24-S		
			●	TL45*-15W-940-B-24-S		
	▲ 36°	1320 lm	3000K	○	TL45*-15W-930-W-36-S	
				●	TL45*-15W-930-B-36-S	
	1420 lm	4000K	○	TL45*-15W-940-W-36-S		
			●	TL45*-15W-940-B-36-S		

*: 4: 3 Phase 4 wires European Track, 6: 3 Phase 6 wires European Dali track

CRI90 12°

3000K




4000K



CRI90 24°

3000K




4000K



CRI90 36°





3000K

4000K




TL44 Tacklight Installation Instructions

Adaptor installation diagram




Packaging:

TL44-S



Box
 L250*W165*H64mm
 1pc/box
 GW: 0.4kg/box



Outer carton
 L520*W350*H350mm
 20pcs/CTN
 GW: 9.2kg/carton